

ZMJ60XDR Density Monitor



ZMJ60XDR Density Monitor

Description

ZMJ60XDR Density Monitors are used to monitor SF₆ gas density in sealed tanks. They are applied to indicate the gas density and to provide signal outputs when the density reaches the set values. Furthermore, it can transmit the real-time SF₆ gas density data remotely, to achieve online remote monitoring function. They are designed to monitor High Voltage systems. They can provide multiple solutions to support new substations and the renovation and upgrading of existing substations.

Features

- Higher accuracy from reference chamber temperature compensation technology.
- Suitable for indoor or outdoor installation.
- Micro-switch that can switch freely between normally open and normally closed points.
- Up to 4 pairs of switches, multiple options such as double alarms and double locks can be realized, making monitoring more secure and reliable.
- High shock resistance, reducing need for oil and the potential hazard of oil leakage.
- Normally closed contact will not false alarm due to vibration.
- RS485 bus interface, easy to expand current system for telemetry and remote control functions.
- Strong EMC capability.

Optionals

- Measuring Medium: SF₆, Air, N₂, SF₆+N₂ and other gases

Application

- SF₆ Gas Insulated Switchgear (GIS)
- SF₆ Insulated Circuit Breaker
- SF₆ Insulated Pole-Mounted Switch
- SF₆ Insulated Transformer
- SF₆ Insulation Current Transformers or Voltage Transformers
- SF₆ Insulated Bus System

Technical Parameters for Remote Module

Operating voltage	10~30VDC	EMC tests	IEC61000-4-2: Level 4 IEC61000-4-3: Level 3 IEC61000-4-4: Level 4 IEC61000-4-5: Level 4 IEC61000-4-6: Level 3 IEC61000-4-8: Level 5 IEC61000-4-9: Level 5 IEC61000-4-10: Level 5
Power consumption	<0.5W		
Communication mode	RS485		
Communication protocol	Modbus RTU		
Baud rate	9600bps		

Technical parameters

Scale range	-0.1 ~ 0.9MPa
Accuracy of set pressure point	±10 kPa @ -30 ~ +60 ° C (gas)
Accuracy of indication	±10 kPa @ -30 ~ +60 ° C (gas)
Accuracy of transmitter	Pressure: ±0.5%FS Temperature: ±1°C Pressure at 20°C: ±1.0%FS
Degree of protection	IP65
Ambient condition	-30°C ~ +60°C , relative humidity: ≤ 95%RH
Leakage rate	≤ 1×10 ⁻⁹ Pa·m ³ /s (Helium leak inspection)
Process connection	M20 x 1.5 (customizable)
Installation method	Radial or Axial
Electrical connection	Pluggable connector, wire diameter 0.2~2.5 mm ²
Insulation property(contact part)	Insulation resistance: >100MΩ (DC500V) Withstand voltage: 2kV, 50/60Hz, 1min
Contact type	Microswitch
Impact rating	50g
Contact electrical parameters	10(1.5)A, 250V AC 0.1(0.05)A, 250V DC
Watch glass	Laminated safety glass
Weight	≈ 1.2kg
Pressure element	Bellow

Dimensions

